

RWS magnum air pistol



RWS/Diana Model-5G MAGNUM -- Power!

To quote the RWS Precision Products Guide:
 "New from Diana, the 5G Magnum, Lite Optic Sights, adjustable trigger, automatic safety and a whopping 700 fps". A major step in Air Pistol development, the 5GM magnum pushes a .177 pellet at rifle velocities using the single stroke break barrel system."

Shaped like the 5-G of old, the 5-GM Magnum is a whole new ballgame. Updated sights, barrelweight with the same comfortable right hand grip. Factory rated at 700-ft/sec**.

The 5-GM has been receiving rave reviews from users everywhere who are excited about it's comfort, accuracy and power. Many have commented on the smoother cocking and crisp trigger.

Right hand thumb rest grip, weight 41 ounces, 18" long, Fiber Optic Sights (fully adjustable), polished steel barrel weight, cocking effort 19 lbs.

NEW! Left Hand Grip
 for 5-G Magnum now available as an accessory(RWS2300LH)

Note: The RWS 5-G Magnum is also sometimes referred to as the 5M 5GM or PS Magnum

**Limited FSI tests chronograph testing confirm velocities of 550 to 630 ft/sec depending on pellet in a new airgun showing this to be one of the most powerful airguns of its type. Velocity usually increase somewhat as the airgun is broken in.

scope mount not available for this handgun at this time

5GM Magnum Air Pistol
 is made in Germany

An all time Customer Favorite
 The 5-G Magnum has outsold all others. Rave Reviews!

RWS 5G-Magnum Air Pistol

stock# RWS AIR PISTOLS .177 Cal. || FSI

RWS/Diana Air Pistol

RWS16925 5-G MAGNUM .177 cal up to 700-fps right hand **198.81**

RWS2300LH Left Hand Grip for RWS 5-G Magnum Checkered Left hand thumb rest grip. Same as factory grip except Left Hand, black. Note: also fits earlier models 5-G, 6-G, 6-M ... 39.83

Tip: If you have both right and left handed shooters sharing the same airgun, you can combine the right panel from the right hand grip set and left hand panel from the left hand grips to make a neutral, ambidextrous grip.

RWS Scopes, mounts, etc.

RWS Airgun Scopes

RWS airguns are equipped with a scope rail for scope mounting. Installing a scope is a simple process requiring a set of rings (also referred to as a scope mount) and the scope. RWS airguns, including barrel cocking and side cocking models, occasionally require an adjustable mount. Most airguns will also need a Scope Stop if it is not built into the mount.

Regular rifle scopes are not recommended for use on airguns as they are not designed to withstand the unique recoil produced by airguns and usually will not focus at typical airgun distances and many do not have the elevation and windage adjustment range that airgunners often expect. Airgun scopes, however, are more durable than "regular" scopes and may also be used on everything from .22 rimfire to magnum centerfire rifles.

All RWS airgun scopes are covered by an RWS limited Lifetime Warranty. All are 1" tube and use standard airgun mounts from RWS and others. **RWS Airgun Scopes** have standard adjusting knobs for windage and elevation. Non-reflective matte finish. The adjustable objective for precise focus at all distances from as close as 7.5 yds. RWS500 and M350 scopes are pre-focused for use from 10m to infinity.

<we also carry a variety of airgun scopes and mounts from Beeman and Bushnell>

BEEMAN Adjustable Scope Mount

The Beeman BEE5039 mount with its built-in scope stop is exceptionally rugged in addition to being easy to install. Fits RWS and other airguns. Use with 1" tube diameter scopes with objective lens to 55mm. Adjustable for Windage and Elevation. Four clamping screws and four screws on each cap assure durability. Suitable for use with all Bushnell and RWS scopes we carry except RWS6975 4x Compact.

NEW -- EZ-Plus 1-Piece Scope Mount

FSI 6400 EZ-Plus Mount with scope stop pin. Today's powerful airguns require a rugged mount to withstand the recoil and vibration. The new EZ-Plus mount fits RWS, Beeman, Gamo and other airguns for use with 1" tube diameter scopes with objective lens to 44 mm. This rugged 1-piece mount includes a built-in scope stop and a long, reversible clamping plate. Simple to install. Three clamping screws and four screws on each cap assure durability. Suitable for use with all Bushnell and RWS scopes we carry Except RWS 350 4x Compact.

NEW RWS0595 2-Pc C-MOUNT and RWS0565 1-Pc C-Mount

The redesigned C-Mount is fully adjustable for both windage and elevation with a built-in Scope Stop, and Auto-Pitch Angulation, high-strength aluminum. The RWS0595 2-pc design allows optimum ring spacing and fits all 1-inch tube scopes to 40mm objective including the RWS350 4x Compact and the M-450 3-9x40mm. RWS0565 1-Piece version is similar -- not for use with compact scopes.

Scope Stop

A Scope Stop or recoil arrestor is required on magnum airguns to keep the mounts from sliding on the rail. A stop is designed into many of today's more popular mounts. If a separate scope is needed see the Beeman FSI 6340, BEE5092 or BEE5093 will so the job on RWS airguns (See page 6 & 10).

BEE 5092 Scope Stop and Raiser Block

BEE 5093 Pro Scope Stop

FSI 6340

BEE 5093 Pro Scope Stop

MUZZLEBRAKE for barrel cocking models

A Muzzlebrake/Barrel-weight is recommended (not required) when adding a scope to RWS airguns. It is a quick and easy 'dress-up' feather that is also quite practical. It forms a comfortable grip when cocking, and enhances the appearance while covering the grooves left when the front sight is removed. Models for most RWS rifles.

RWS has discontinued plans for a new muzzlebrake, but fortunately, the attractive BEE7129 Muzzlebrake from Beeman is compatible and quite easy to install. It is not necessary to make any modification to the barrel - simply remove the front sight and install. The BEE7129 fits all current RWS/Diana barrel cocking airguns - Models 34, 36, 38, 40, 45 and 350. Not suitable for sidelever or underlever models. See page 10.

Installing the BEE7129 Muzzlebrake as simple as A-B-C

After removing the front sight, simply:

- Select one of the shims that best fits your barrel (thicker shim for slimmer barrels) and slide it on.
- Slide the Muzzlebrake over the muzzle. No hammering is required. The unique internal cone automatically centers on the barrel.
- Slide the shim into place and tighten the set screw with the wrench supplied. (recheck tightness after initial use)

NOTICE: make sure the airgun is unloaded and uncocked



RWS Scope Mounts & Sight Accessories

stock# RWS AIRGUN SCOPES || FSI

RWS6980 RWS M-500 4x32mm Airgun Scope Fixed Focus 10m to Infinity.

With rigid 2-Piece RWS Mounts included. 64.86
EXTRA SALE - Limited Time 49.84
 (not suggested for M48/52/54/350/460 rifles)

RWS6970 RWS M-300 4x32mm Air Rifle Scope, 1-in tube, matte finish, adjustable objective from 25 ft to infinity, haze filter lens caps **SALE .. 79.87**

RWS6975 RWS M-350 4x32mm Compact Air Rifle Scope, 1-in tube, matte finish, fixed focus, haze filter lens caps. Note: requires 2-piece rings 68.86

RWS6978 RWS M-450 3-9x40mm Airgun Scope Variable power, objective focus. ~~Now Just 49.84~~
Huge Factory sale 69.91
 (also see Beeman and Bushnell airgun scopes)

stock# SCOPE MOUNTS, SIGHTS, Acces. || FSI

RWS0595 **RWS C-MOUNT, fully adjustable.** 2-piece, with built-in Scope Stop **EXTRA SPL 39.93**

RWS0565 **RWS C-MOUNT, fully adjustable.** 1-piece, with built-in Scope Stop **NEW 49.94**

BEE5039 **Beeman Deluxe 1-pc Adjustable Mount 89.88**

FSI 6400 **EZ-Plus 1-Pc Scope Mount 33.83**

FSI 6340 **Recoil Arrestor scope stop SALE 8.88**

SCOPE STOP, see Beeman BEE5093 and Beeman 5092 on page 10

MUZZLEBRAKE/Barrel Weight

BEE7129 for M-350, M-45, M-34, M-36, M-38 Rifles Easy to install, attractive, practicalSee page 10 for M-48, M-52, M-54 Riflesnone available

stock# RWS ACCESSORIES || FSI

SLING SWIVEL SET: Complete with Barrel Band, wood stud, 1" detachable swivels, for RWS 45,34,36,38, 350, 40 use BEE7440 + BEE7410....page 13

Other Accessories: see Beeman

RWS3300001 **M48/52/54 COCKING ROD** (Threaded Rod) replacement rod for RWS **M48/52/54** (use your original nuts & clips) 19.88

RWS3300350 **BREECH SEAL** o-ring for 350, 34,36,40 5.85

RWS3300005 **BREECH SEAL** o-ring for 5G/ P5, 6M, 6G. 5.85

Airgun Targets

See FSI Airgun Targets page 16

Beeman Airgun Targets and Pellet Traps page 13

RWS Airgun Scopes and Mounts to realize your airgun's full potential

RWS RIFLE SCOPES - 1" tube diameter

Model	Power	diameter	Objective	Focus Length (in.)	Wt (oz.)	Finish
M-500*	4x	32mm	fixed	11 1/2	11.5	satn
*2-pc rigid rings included with M-500						
M-300	4x	32mm A.O.	7.5 m	11 1/4	13.2	satn
M-350**	4x	32mm	fixed	7/8	11.5	satn
**compact scope use 2-piece rings - eyepiece focus						
M-450	3-9x	40mm A.O.	10 m	12 1/2	14.3	satn
Haze filter lens caps are included with all models						

RWS Airguns are FUN!

RWS Airguns are protected by the RWS Limited Lifetime Warranty!

Airgun Comparison Table

RWS Airgun Comparison Table

(from various RWS sources - specifications may vary with caliber)

RIFLES	Weight (lbs.)	Length (in.)	Effort (lb.)	Cocking Muzzle Veloc. (ft/Sec.)		trigger pull (lb.)	Barrel Length (in.)
				.177	.22		
Barrel Cocking							
M-34	7.5	45	33	1,000	800	3.3	19.5
Pro	8	46	29	1,000	---	3.3	19.8
Pro Compact	7.8	42	33	1,000	---	3.3	15.8
M-34 Panther	7.2	45	33	1,000	800	3.3	19.8
Panther Pro	8.5	46	30	1,000	---	3.3	19.8
Pro Compact 8	42	33	1,000	---	3.3	15.8	
M-40	7.7	45	33	1,000	---	3.3	19.8
Schutze (youth)	5.7	41	19	580	---	5	16.5
M-350M (Dlx)	8.5	48	33	1,250	1,000	3.3	19.5
Feuerkraft	8	48	33	1,250	1,000	3.3	19.6
Feu Pro Com	8.5	45	42	1,250	1,000	3.3	15.8
Side Lever Cocking							
M-48	9	43	39	1,100	900	3.3	17
M-52	9	44	39	1,100	900	3.3	17
M-52 Luxus	8.8	44	39	1,100	900	3.3	17
M-54	10	44	39	1,100	900	3.3	17
Under Lever Cocking							
M-460	8.3	45	36	1,350	1,150	3.3	18.4
PISTOLS							
5-G Magnum	2.8	18	28	700*	---	3.3	9

all RWS airguns are protected by the RWS Limited Lifetime Warranty